

PATENT ABSTRACTS OF JAPAN

引用例

Reference No. 1

(11)Publication number : 11-244098

(43)Date of publication of application : 14.09.1999

(51)Int.Cl.

A47C 27/04

A47C 27/05

A47C 27/06

(21)Application number : 10-061976

(71)Applicant : NIPPON BED SEIZO KK

(22)Date of filing : 27.02.1998

(72)Inventor : USAMI NOBUO

(54) MATTRESS FOR BED

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a mattress of which the number of production processes can be reduced and durability is improved by controlling an excessive deflection of side parts due to an eccentric load on edges.

SOLUTION: A border cushion material 2 and a border quilt 5, a top face cushion material 3 and a top face quilt 6, an underside cushion material 4 and an underside quilt 7 are respectively adhered to each other through a synthetic resin adhesive. The underside of the top face cushion material 3 and the top face of the underside cushion material 4 are respectively adhered to the top faces and the undersides of bag bodies 11 of numerous pocket coils 10 constituting a spring unit 1. The peripheral parts of the top face cushion material 3 and the underside cushion material 4 are projected from the outer periphery of the spring unit 1 by a length substantially corresponding to the thickness of the border cushion material 2 and butted with both upper and lower end faces of the border cushion material 2.

